

Please amend the claims as follows:

COPY OF PAPERS
ORIGINALLY FILED

- Sub
B1
A1
1. (Amended) An apparatus comprising:
a substrate having a first surface, wherein the first surface of the substrate contains
a first plurality of fasteners of one of a plurality of hook and loop
mechanisms and each of the first plurality of fasteners including one of a
first fastener type;
a cable fastener comprising a single type of fastener of the one of the plurality of
hook and loop mechanisms, wherein the single type of fastener is
configured to engage the first fastener type, wherein the cable fastener is
separate from the substrate; and
wherein the cable fastener is further shaped to define:
a variable-width opening,
an elongated body having a predetermined width,
a head portion at one end of the body, the head portion having a width
greater than the predetermined width,
the head defining an opening through which the head of the cable fastener
may be pulled;
 2. The apparatus recited in Claim 1, wherein the plurality of hook and loop mechanisms
includes one or more mushroom-shaped stems.
 3. The apparatus recited in Claim 1, wherein the plurality of hook and loop mechanisms
includes one or more pine-tree-shaped stems.
 4. The apparatus recited in Claim 1, wherein the plurality of hook and loop mechanisms
includes one or more hooks.
 5. The apparatus recited in Claim 1, wherein the plurality of hook and loop mechanisms
includes one or more loops.
 6. The apparatus recited in Claim 1, wherein the substrate is planar.

7. (Amended) The apparatus recited in Claim 1, further comprising a rigid frame.

COPY OF PAPERS
ORIGINALLY FILED

8. The apparatus recited in Claim 7, wherein the frame includes at least one planar surface.

9. The apparatus recited in Claim 7, wherein:
the substrate includes a second surface substantially opposite the first surface; and
the second surface of the substrate is coupled to the frame.

Claim 10 has been cancelled.

11. (Amended) A method of managing cable, comprising:
supporting one or more cables with a cable fastener, the cable fastener being shaped
to be capable of defining a variable-width opening, wherein the cable
fastener contains one of a plurality of hook and loop mechanisms;
releasably engaging the cable fastener to a substrate, wherein the substrate contains
another of the plurality of hook and loop mechanisms; and
providing a rigid frame capable of accommodating a plurality of fiber cables;

12. The method recited in Claim 11, wherein the plurality of hook and loop mechanisms
includes one or more mushroom-shaped stems.

13. The method recited in Claim 11, wherein the plurality of hook and loop mechanisms
includes one or more pine-tree-shaped stems.

14. The method recited in Claim 11, wherein the plurality of hook and loop mechanisms
includes one or more hooks.

15. The method recited in Claim 11, wherein the plurality of hook and loop mechanisms
includes one or more loops.

16. The method recited in Claim 11, wherein the substrate is planar.

Claim 17 has been cancelled.

B1
cont

18. (Amended) The method recited in Claim 11, wherein the frame includes at least one planar surface.

AI
cont

19. (Amended) The method recited in Claim 11, further comprising:
coupling a second surface of the substrate to the frame, wherein the second surface
is substantially opposite the first surface of the substrate.

20. The method recited in Claim 11, wherein the cable fastener is further shaped to define:
an elongated body having a predetermined width; and
a head portion at one end of the body, the head portion having a width greater than the
predetermined width;
the head defining an opening through which the head of the tie wrap may be pulled.

21. The method recited in Claim 11, wherein the cables comprise one or more fiber optic
cables.

22. The method recited in Claim 11, wherein the cables comprise one or more electrical cables.

23. (Amended) An apparatus comprising:
a means for supporting one or more cables, wherein the means for supporting one
or more cables includes a cable fastener means;
a means for releasably engaging the cable fastener means; and
a frame means for supporting one or more fiber cables configured to receive the
cable fastener means.

24. The apparatus recited in Claim 23, wherein the means for releasable engagement includes
one or more mushroom-shaped stems.

25. The apparatus recited in Claim 23, wherein the means for releasable engagement includes
one or more pine-tree-shaped stems.

26. The apparatus recited in Claim 23, wherein the means for releasable engagement includes
one or more hooks.

B1
Cont

27. The apparatus recited in Claim 23, wherein the means for releasable engagement includes one or more loops.

28. **(Amended)** The apparatus recited in Claim 23, further comprising:
a substrate means.

AI
Cont

Claim 29 has been cancelled.

30. **(Amended)** The apparatus recited in Claim 23, further comprising:
a substrate means; and
a means for coupling the substrate means to the frame means.

31. The apparatus recited in Claim 23, wherein the cable fastener means further comprises:
a means for encircling the one or more cables such that each of the one or more cables is squeezed into contact with at least one other of the one or more cables.

32. The apparatus recited in Claim 23, wherein the one or more cables comprise one or more fiber optic cables.

33. The apparatus recited in Claim 23, wherein the one or more cables comprise one or more electrical cables.

34. An apparatus for managing cable, comprising:
a rigid frame capable of accommodating a plurality of cables, the frame having at least one planar surface;
a planar substrate having a first surface and a second surface, the second surface being substantially opposite the first surface, the first surface of the substrate containing a plurality of engagement mechanisms, the second surface of the substrate being coupled to the planar surface of the frame; and
a tie wrap containing loops capable of engaging the engagement mechanisms of the substrate, wherein the tie wrap is thereby capable of being releasably engaged to the substrate by means of a hook and loop connection, and wherein the tie wrap is shaped to define:
an elongated body having a predetermined width; and
a head portion at one end of the body, the head portion having a width greater than the predetermined width, and defining an opening through which the body of the tie wrap may be pulled.

35. The apparatus recited in Claim 34, wherein the hooks are mushroom-shaped stems.

36. The apparatus recited in Claim 34, wherein the plurality of cables comprises a plurality of fiber optic cables.

37. The apparatus recited in Claim 34, wherein the plurality of cables comprises one or more metal cables.